

DATA SHEETS



PRODUCT NAME:

DELTA SHEETS

PRODUCT CODE/S:

PREPACKED 5 PER PACK W94XH94: PPA010, PPA011, PPA012, PPA013 50 PER PACK W94XH94: AP195, AP196, AP197 PREPACKED 5 PER PACK W105XH105: PPA014, PPA015, PPA016, PPA017

KEY FEATURES:

Safeline High performance corner and detail sanding triangles Keeps abrasive grit firmly bonded to the backer for increased lifespan

- •Allows fast stock removal with reduced clogging on gummy, resinous timbers, fillers and paint removal
- Ideal for use on wood, paint, metal and plaster

MATERIAL:

Aluminium Oxide


This man-made material is suitable for shaping, sanding and polishing hard metal such as iron and steel, but also effective on timber. Aluminium oxide cuts much faster and lasts longer than glass or garnet.


It is available on non-waterproof, cloth or waterproof backings.

SIZE CHART

| GRIT SIZE | GRADE | CODES | SIZE | APPLICATION |
|-------------|----------------------|--------------|---------------|------------------|
| 40-60 | COARSE | PPA012 | 95MM X95MM | MATERIAL REMOVAL |
| 80-100 | MEDIUM | PPA011 | 95MM X95MM | LEVELING |
| 120-UPWARDS | FINE | PPA010 | 95MM X95MM | FINISHING |
| ASSORTED | FINE, MEDIUM, COARSE | PPA013 | 95MM X95MM | |
| 40-60 | COARSE | PPA016 | 105MMX105MM | MATERIAL REMOVAL |
| 80-100 | MEDIUM | PPA015 | 105MMX105MM | LEVELING |
| 120-UPWARDS | FINE | PPA014 | 105MMX105MM | FINISHING |
| ASSORTED | FINE, MEDIUM, COARSE | PPA017 | 105MMX105MM | |
| 40-60 | COARSE | AP185, AP186 | 100MM X 147MM | MATERIAL REMOVAL |
| 80-100 | MEDIUM | AP188 | 100MM X 147MM | LEVELING |
| 120-UPWARDS | FINE | AP189 | 100MM X 147MM | FINISHING |

| GRIT SIZE | GRADE | CODES | SIZE | APPLICATION |
|-------------|----------------------|------------------------|-------------|------------------|
| 120-UPWARDS | FINE | AP195, AP197, AP196 | 94MM X 94MM | FINISHING |
| 40-60 | COARSE | | | MATERIAL REMOVAL |
| 80-100 | MEDIUM | | | LEVELING |
| 120-UPWARDS | FINE | | | FINISHING |
| ASSORTED | FINE, MEDIUM, COARSE | | | |
| 40-60 | COARSE | | | MATERIAL REMOVAL |
| 80-100 | MEDIUM | | | LEVELING |
| 120-UPWARDS | FINE | | | FINISHING |
| ASSORTED | FINE, MEDIUM, COARSE | | | |





STORAGE

IT IS RECOMMENDED THAT ALL COATED ABRASIVE PRODUCTS SHOULD BE STORED AT CONSTANT LEVELS OF TEMPERATURE AND HUMIDITY WITHIN THE RANGES OF 18-22°C, 50-65% RH. THEY SHOULD BE KEPT AWAY FROM DAMP (OR COLD) WALLS, WINDOWS OR FLOORS TO AVOID POSSIBLE MOISTURE ABSORPTION. EQUALLY STORAGE ADJACENT TO HEAT SOURCES E.G. STEAM PIPES, RADIATORS, HOT AIR DUCTS, OVENS, ETC.,



















