


PRODUCT NAME:

ALCON M5513 G/P SILICONE 285ML

PRODUCT CODE/S:

EBGPGALCONBLK
EBGPGALCONWH

KEY FEATURES:

ALCON M5513 GENERAL PURPOSE SILICONE IS A HIGH-QUALITY, ACETOXY-CURE SILICONE SEALANT DESIGNED FOR UNIVERSAL SEALING APPLICATIONS WHERE DURABILITY, WEATHER RESISTANCE, AND FLEXIBILITY ARE ESSENTIAL. IT ADHERES EXCELLENTLY TO MOST NON-POROUS SURFACES SUCH AS GLASS, CERAMICS, METAL, AND PLASTIC. THIS SEALANT IS AVAILABLE IN BLACK AND WHITE TO SUIT A VARIETY OF FINISHES AND DECORATIVE NEEDS. PERFECT FOR GLAZING, SANITARY APPLICATIONS, AND GENERAL SEALING JOBS IN DOMESTIC AND COMMERCIAL SETTINGS.

- AVAILABLE IN BLACK AND WHITE
PERMANENTLY FLEXIBLE AND WATERPROOF
EXCELLENT ADHESION TO GLASS, CERAMIC, METALS, AND PLASTICS
MOULD-RESISTANT – SUITABLE FOR SANITARY AREAS
FAST SKINNING AND CURING TIME
IDEAL FOR INTERIOR AND EXTERIOR USE
EASY TO TOOL AND APPLY

DETAILS:
TECHNICAL SPECS:

Type: Acetoxy silicone
Curing System: Moisture cure
Colours: Black / White
Packaging: 285ml cartridge
Skin Time: Approx. 10 minutes @ 20°C
Cure Rate: ~2mm in 24 hours
Movement Capability: ±12.5%
Application Temperature: +5°C to +40°C
Service Temperature: -40°C to +150°C

IDEAL FOR:

- Sealing window and door frames
- Sanitary joints in kitchens and bathrooms
- Glazing and weatherproofing tasks
- General household and trade use
- Draught and leak sealing
- Interior and exterior applications

INSTRUCTION FOR USE:

- Surface Prep: Ensure all surfaces are clean, dry, and free from grease, dust, and loose materials.
Application: Cut nozzle to desired bead size. Apply using a standard caulking gun.
Tooling: Smooth within 5–10 minutes using a wet finger or silicone finishing tool.
Cure Time: Allow to fully cure before exposing to water or pressure (typically 24 hours for 2mm depth).
Cleanup: Wipe off excess with white spirit while uncured. Cured silicone must be removed mechanically.

STANDARDS

EN 15651-1