



PRODUCT NAME:

EVERBUILD SEALANT PRIMER 3N 1 LITRE

PRODUCT CODE/S:

EBSP122239

KEY FEATURES:

EVERBUILD SEALANT PRIMER 3N (1 LITRE) IS A SOLVENT-BASED, ONE-COMPONENT PRIMER DESIGNED TO ENHANCE THE ADHESION OF SEALANTS TO VARIOUS SUBSTRATES. IT IS PARTICULARLY EFFECTIVE FOR PREPARING POROUS SURFACES SUCH AS CONCRETE, MASONRY, AND METALS BEFORE THE APPLICATION OF SEALANTS

- **ENHANCED ADHESION:** IMPROVES BOND STRENGTH BETWEEN SEALANTS AND SUBSTRATES, ENSURING A DURABLE SEAL.
- **WATER REPELLENT:** OFFERS PROTECTION AGAINST MOISTURE, PREVENTING POTENTIAL SEALANT DEGRADATION.
- **SHORT FLASH-OFF TIME:** ALLOWS FOR QUICKER APPLICATION OF SEALANTS AFTER PRIMING.
- **EASY APPLICATION:** CAN BE APPLIED USING A BRUSH OR ROLLER FOR UNIFORM COVERAGE.
- **TRANSPARENT FINISH:** DRIES CLEAR, MAINTAINING THE AESTHETIC OF THE SUBSTRATE.

DETAILS:

TECHNICAL SPECS:

Type: Solvent-based, one-component primer

Packaging: 1 Litre bottle

Shelf Life: Approximately 9 months from the date of production, if stored in undamaged, original, sealed packaging, and under appropriate storage conditions .

Application Temperature: +5°C to +40°C

Storage Conditions: Store in a cool, dry place away from direct sunlight and sources of heat.

IDEAL FOR:

- **Surface Preparation:** Ensure that all surfaces are clean, dry, and free from dust, grease, and other contaminants.
- **Application:** Apply the primer evenly using a clean brush or roller.
- **Drying Time:** Allow the primer to dry until it is touch dry before applying the sealant.
- **Sealant Application:** Proceed with the application of the chosen sealant according to the manufacturer's instructions.

INSTRUCTION FOR USE:

- **Surface Preparation:** Ensure all surfaces are clean, dry, and free from contaminants such as dust, grease, oils, and loose particles.
- **Application:** Stir the primer well before use. Apply the primer evenly using a clean brush or a roller to the prepared surface.
- **Drying Time:** Allow the primer to dry until it is touch dry, which typically takes around 15-30 minutes depending on temperature and humidity.
- **Sealant Application:** Once the primer has dried, proceed with the application of the chosen sealant, following the manufacturer's instructions for the specific sealant.

STANDARDS

EN 15651-1