



## PRODUCT NAME:

HPSA MPS WHITE/CLEAR 300ML

## PRODUCT CODE/S:

EVTHPSAMPSC, EVTHPSAMPSW

## OVERVIEW

THE HPSA MPS SILICONE SEALANT IS A PREMIUM, ONE-COMPONENT, NEUTRAL-CURE SILICONE IDEAL FOR BOTH INTERIOR AND EXTERIOR APPLICATIONS. IT OFFERS SUPERIOR ADHESION TO A WIDE RANGE OF NON-POROUS SUBSTRATES, INCLUDING UPVC, GLASS, CERAMICS, AND METALS. ITS FLEXIBLE FORMULATION ACCOMMODATES MOVEMENT AND PROVIDES LONG-LASTING SEALS RESISTANT TO WEATHERING AND AGING.

THE WHITE VARIANT IS PARTICULARLY SUITED FOR SANITARY AND CLEAN ENVIRONMENTS, ENSURING CLEAN, PROFESSIONAL APPLICATIONS.

## DETAILS:

### Key Features:

- Neutral-curing silicone suitable for various substrates
- Excellent adhesion to uPVC, glass, ceramics, and metals
- Flexible and durable, accommodating movement
- Resistant to weathering, aging, and UV exposure
- Available in Clear and White for aesthetic versatility
- Ideal for sanitary and clean environments (White variant)

### Technical Specifications:

1. Base: Neutral-curing silicone  
Colours: Clear, White  
Packaging: 300ml cartridge  
Movement Accommodation: Up to 25%  
Application Temperature: +5°C to +40°C  
Service Temperature: -40°C to +150°C  
Skin Formation Time: Approximately 15-25 minutes  
Curing Rate: ~2-3 mm/24 hours  
Shelf Life: 12 months when stored in cool, dry conditions

### DIRECTIONS FOR USE

1. Ensure surfaces are clean, dry, and free from grease.  
  
Cut the nozzle to the desired bead size and apply using a caulking gun.  
  
Tool the sealant within 5-10 minutes for a smooth finish.  
  
Allow to cure; full cure achieved in 24-48 hours depending on joint depth and conditions.  
  
Clean tools and excess sealant with a suitable cleaner before curing.

## STANDARDS

EN 15651-1