



PRODUCT NAME:

PORTABLE GAS HEATER

PRODUCT CODE/S:

HEAT1010

KEY FEATURES:

STAY WARM AND COMFORTABLE WHEREVER YOU ARE WITH THIS GAS CARTRIDGE SPACE HEATER, FEATURING DUAL POWER SETTINGS OF 1000W AND 2000W TO MEET YOUR HEATING NEEDS. DESIGNED FOR PORTABILITY AND CONVENIENCE, THIS HEATER OPERATES ON BUTANE OR PROPANE GAS CARTRIDGES, MAKING IT PERFECT FOR CAMPING, OUTDOOR GATHERINGS, AND EMERGENCY INDOOR USE.

- SAFETY FEATURES:**
 - PILOT FLAME:** ENSURES A STEADY, RELIABLE IGNITION FOR THE HEATER. IT PREVENTS GAS FLOW UNTIL THE PILOT FLAME IS ESTABLISHED, REDUCING THE RISK OF GAS LEAKS.
 - FLAME SUPERVISION DEVICE (FSD):** AUTOMATICALLY CUTS OFF THE GAS SUPPLY IF THE FLAME IS ACCIDENTALLY EXTINGUISHED, PREVENTING UNBURNED GAS FROM LEAKING.
 - OXYGEN DEPLETION SENSOR (ODS):** MONITORS THE OXYGEN LEVELS IN THE ENVIRONMENT AND AUTOMATICALLY SHUTS OFF THE HEATER IF IT DETECTS LOW OXYGEN LEVELS, REDUCING THE RISK OF CARBON MONOXIDE BUILDUP.
 - TILT SWITCH:** AUTOMATICALLY TURNS OFF THE HEATER IF IT IS KNOCKED OVER, ENSURING SAFETY IN CASE OF ACCIDENTAL TIPPING.

DETAILS:

TECHNICAL SPECS:

Power Output	1 kW (1000 Watts) and 2 kW (2000 Watts)
Voltage	220-240V / 50Hz
Heating Element	Ceramic
Fan	Integrated high-efficiency fan
Thermostat	Adjustable

Key Features:

- 3 Adjustable Heat Settings (Low, Medium, High)
- Ceramic Burner Technology – Rapid, efficient heat distribution
- Push-Button Ignition System – No matches or lighters needed
- Flame Failure & Oxygen Depletion Safety Systems
- Built-in Gas Cylinder Storage Compartment
- Fitted with Castor Wheels for Easy Portability
- Ideal for Temporary Heating in Well-Ventilated Spaces

Technical Specifications:

- Fuel Type: Butane Gas
 Heat Output: Approx. 4.2 kW max
 Burner Type: Ceramic Plate
 Ignition: Piezo push-button
 Safety: ODS and Flame Failure Protection
 Mobility: 4 swivel castor wheels
 Dimensions: Approx. 720 x 420 x 350 mm

STANDARDS

EN 449:2002