



PRODUCT NAME:

TIGER ROLL SURFACE PROTECTOR

PRODUCT CODE/S:

PGP25:30M X 60CM GLASS PROTECTOR FILM
PGP100:100M X 60CM GLASS PROTECTOR FILM

KEY FEATURES:

Protects against scratches, stains, dust and dirt.
Ideal protection for plastering, painting and decorating.
Suitable for most windows, glazed doors and smooth glass surfaces.
Reverse wound for easy application.
One person easy application for single use only.
Easily removed after use with no sticky residue when removed within 30 days.
Heavy-duty rip-resistant material.
Low-adhesion acrylic adhesive designed for smooth surfaces.

DETAILS:

Installation

- Remove film from the surface within 30 days. Failure to remove the film may cause damage to the finished surface.
- Perform a compatibility test on a small, hidden area before full application for no longer than 48 hours.
- Abnormal heat conditions can change the chemistry of adhesion and may result in overheating or underheating and may cause issues when the tape is removed, it is advised to check removal on a daily basis.
- Do not use on surfaces that are not fully cured.
- Do not use on glass, natural marble or stone, carpet, damp surfaces or unfinished wood.
- Operating temperatures: +5°C to +25°C.
- Store at room temperature for one day before use.
- Not recommended for use with underfloor heating.
- The surface should be clean and dry prior to installation.

Product Specifications

Specification	Details
Construction:	Low-density polyethylene film with an acrylic-based pressure-sensitive adhesive on one side.
Film Thickness:	50 Micron
Adhesion:	0.29 N/25mm (Low Adhesion)
Moisture Resistance:	Good
Oil Resistance:	Moderate
Solvent Resistance:	Moderate
UV Resistance:	Indoor applications only
Storage Temperature:	+5°C to +25°C
Shelf Life:	36 months from the date of manufacture

Important Notice

Every effort has been made to ensure that the information provided is accurate and reliable. However, due to variations in processing conditions and applications beyond our control, users are advised to confirm the suitability of this product through their own testing. Tiger Roll cannot accept responsibility for any loss or damage arising from the use of this information or product

STANDARDS